

DESCRIPTION - 020 SEAM CEMENT

Recommended for seaming selvage edge and cross joints on most carpets including sponge and foam-backed carpet. Not recommended for vinyl-backed carpets. Non-photochemically reactive per rule 102.

APPLICATION - FOR PROFESSIONAL USE ONLY

1. Cement is ready for use. Pour into polyurethane squeeze bottle.
2. Apply a 1/8" bead of adhesive along the entire edge of the "primary" back on one piece of carpet to be seamed. Butt the other piece of carpet to be seamed to the first piece for proper adhesive transfer and to secure the seam.
3. Remove any excess seam cement by rubbing with a clean white rag dampened with an adhesive remover/stripper.
4. Return seam cement to the container after use. Do not store in plastic squeeze bottle.

PHYSICAL PROPERTIES

Base:	Synthetic Rubber, Resin Blend
Appearance:	Thin amber syrup
Odor:	Solvent
Tracer:	Does not contain fluorescent tracing agents
Shelf Life:	One year in unopened container at 70° F.
Coverage:	Up to 1,000 linear feet per gallon.
Clean-Up:	Adhesive remover/stripper

DANGER

FLAMMABLE! TOXIC! VAPORS MAY IGNITE EXPLOSIVELY. Prevent build-up of vapors. Open all windows and doors. Use only with cross ventilation. Keep away from heat, sparks and open flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Close container after use. KEEP OUT OF REACH OF CHILDREN! Harmful or fatal if swallowed. If swallowed, do not induce vomiting. Call Physician immediately. Avoid breathing vapors. Avoid prolonged or repeated contact with skin or contact with eyes. Contains Aliphatic hydrocarbons, Toluene, and Methyl Ethyl Ketone. Complies with Consumer Product Safety Commission ban on extremely flammable contact cements. Flash point of this cement is over 20° F.T.O.C.

WARRANTY INFORMATION

For warranty information, call Technical Services at (706) 712-5823, visit us on the web at www.powerhold.com.com/msds. Flooring manufacturer's and Powerhold's written pre-installation and installation instructions must be strictly followed or the Powerhold warranty will be void.

SELLER MAKES NO OTHER WARRANTY OR GUARANTEE OF ANY KIND REGARDING FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. BUYER ASSUMES FULL RESPONSIBILITY FOR QUALITY CONTROL, TESTING AND DETERMINATION OF SUITABILITY OF PRODUCT FOR ITS INTENDED APPLICATION OR USE.