

DESCRIPTION

525 is a non-wrinkling, all purpose spray adhesive. It bonds to most materials including carpet, tile, fabrics, wood, rubber artwork, leather, etc.

INSTRUCTIONS

Shake well before using. For best results, hold can 8" to 12" from surface to be bonded and apply uniform coat.

Permanent bond: Coat both surfaces evenly. Allow 30 seconds dry time before assembly. Bonds should be made while adhesive is wet and aggressively tacky.

Non-permanent bond: For easy removable applications, apply a light coat to one surface and allow to dry at least 5 minutes before mounting. Surfaces can then be separated when desired.

CLEANUP

Invert can and depress tip until adhesive is cleared. Clean up overspray and smears with naphtha or turpentine. Replace cap and store in a cool place, away from direct sunlight.

COVERAGE

* Coverage is approximate and may vary depending on porosity of substrate.

**IT IS THE INSTALLER'S RESPONSIBILITY TO APPLY THE PROPER AMOUNT OF ADHESIVE FOR THE JOB CONDITION.

OTHER PROPERTIES

Appearance: Light yellow liquid

Shelf life: One year in unopened container at 70° F

CALIFORNIA PROPOSITION 65:**WARNING**

This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm. Contains Acetone [CAS 67-6L.j-1), Hexane [CAS 110-5L.j-3), Propane [CAS 7L.j-98-6), Dimethyl Ether [CAS 115-10-6), and NJTSRN801000L.j9-5029P.

CAUTION

EXTREMELY FLAMMABLE. DO NOT take internally. KEEP OUT OF REACH OF CHILDREN. If swallowed, DO NOT induce vomiting. Call a physician immediately.

WARRANTY INFORMATION

For warranty information, call Technical Services at (706) 712-5823, visit us on the web at www.powerhold.com.com/msds. Flooring manufacturer's and Powerhold's written pre-installation and installation instructions must be strictly followed or the Powerhold warranty will be void.

SELLER MAKES NO OTHER WARRANTY OR GUARANTEE OF ANY KIND REGARDING FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. BUYER ASSUMES FULL RESPONSIBILITY FOR QUALITY CONTROL, TESTING AND DETERMINATION OF SUITABILITY OF PRODUCT FOR ITS INTENDED APPLICATION OR USE.